



# PRINT & CHECK EVO-TE

CARTON SERIALIZATION STATION

## QUICK COMPLIANCE, MINIMUM SPACE

- Compact footprint module integrating **add-on tamper evident** function to serialization features.
- **Fully compliant with EU-FMD** regulatory requirements.
- Tamper evident seal application unit for airplane or reverse tuck cartons.
- Double belt conveyor allows precise handling of cartons.

- Quick and easy deployment
- Line speed up to **300 cartons/minute**
- Conveyor length: **1400 mm**
- Up to 4 TIJ printing heads
- Single HMI to manage settings of all installed functions

INLINE	OFFLINE
TIJ	LASER
SIDE PRINTING	TOP PRINTING
TOP LABELLING	TAMPER EVIDENT
CHECKWEIGHER	RFID



THERMAL INKJET PRINTING



TAMPER EVIDENT




## STANDARD TECHNICAL FEATURES

<b>Track &amp; Trace inspection cameras</b>	Up to 2
<b>Transport system</b>	DOUBLE BELT CONVEYOR
<b>Standard belt pitch</b>	150 mm
<b>Working height</b>	800-1000 mm
<b>Rejection system</b>	AIR PRESSURE, 200 l/min @ 6 bars Optional: pneumatic
<b>HMI</b>	15" IPC TOUCH SCREEN
<b>Network connectivity</b>	GIGABIT ETHERNET
<b>Power supply</b>	3.6 kW, UPS sustained
<b>Rated voltage</b>	L/N/PE 230 V (options depending on local standards)
<b>Electrical cabinet</b>	PLC, safety controls, power supply modules, communication modules
<b>Frame structure</b>	STAINLESS STEEL
<b>Machine net weight</b>	550 kg

## STANDARD DIMENSIONAL RANGE

### CARTON SIZE (mm)

	MIN	MAX
<b>A</b>	35	120
<b>B</b>	15	100
<b>C</b>	50	250



### TAMPER EVIDENT ROLL

	mm
External roll	280
Internal roll	76
Label width	40 max

